

SCROLL CROSS ARM INSTALLATION:

A ONE PIECE CAST ALUMINUM SCROLL CROSS ARM IS MOUNTED ON A 3" TENON. AN INJECTION MOLDED, UV STABILIZED POLYCARBONATE POST TOP FITTER WILL BE MOUNTED TO EACH TENON WITH STAINLESS STEEL SET SCREWS. ADAPTER WILL BE SUPPLIED AS NECESSARY, BY CLP.

THE POST TOP FITTER UNIT IS FOR DIFFUSERS WITH A STANDARD 5 INCH TO 5.25 INCH BOTTOM OPENING. THE DIFFUSER WILL BE SECURED TO THE FITTER WITH TWO SPRING LOADED WING CLAMPS.

ELECTRICAL:

THE POST TOP FITTER IS FOR NON-BALLASTED LAMP APPLICATIONS. MAX WATTAGE IS DETERMINED BY THE LAMP USED.

DIFFUSER OPTIONS:

POLYCARBONATE CLEAR POLYCARBONATE WHITE

LAMP OPTIONS:

LED CFL INC

VOLTAGE:

120 V

NEW ENGLAND POST BASE OPTIONS:

ANCHOR BASE BURIAL BASE

NOTES:

1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.

SOIL

5" SQ.

PREMIXED

WATER

CONCRETE AND

BURIAL BASE

- 2. ALL DIMENSIONS ARE CONSIDERED TRUE AND REFLECT MANUFACTURER'S SPECIFICATIONS.
- 3. DO NOT SCALE DRAWING.
- 4. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.CADdetails.com/info REFERENCE NUMBER 4197-076.



NEW ENGLAND POST SERIES - N6 10'-6" WITH CROSS ARMS AND ROUND GLOBE LUMINAIRE (\$16)

GALVANIZED

STEEL PIPE

FOAM

(LLDPE)

POLYSTEEL PIPE

Ø3 3/8" -

CONDUIT HOLE SUPPLIED

BURIAL BASE

CLOSED CELL

POLYURETHANE

POLYETHYLENE

LINEAR LOW DENSITY

2 1/4" O.D.

COUPLING AND

10"

CONDUIT NOT SUPPLIED BY

CLP.

Ø12.00

3 1/2"

5 1/2"

6 1/2"