A Height 36"	TGRAGAGAS
$\begin{array}{c} & & \\ & & \\ \hline & \\ & \\ & \\ & \\ & \\ & \\ &$	for <i>RUST FREE LIFE</i> . The Fitter is 3 inches in diameter. The fixture finish is a thermoplastic modified Nitocelloucs coating. All electrical components are UL recognized. This fixture has a UL label and is suitable for wet locations. Sockets
Photometrics A= Height Lamp ~ 150 HPS Lumens ~ 16000 B= Width Mounting Height ~ 12 Feet Lens ~ Clear	are medium and mogul for HID use and have nickel plated screw shell with center contacts 1500W pulse rated. All ballast are UL approved factory wired and pre-tested. <u>Colors:</u> All 53 colors, Powder Coating Available Contact Factory. <u>Lens:</u> Polycarbonate
$12' \underbrace{\frac{10}{5}}_{\text{Foot Candle 5'}} \underbrace{\frac{20}{2.25}}_{\text{SO}} \underbrace{\frac{30}{.50}}_{.20} \underbrace{\frac{40}{.20}}_{.20} \underbrace{\frac{50}{.10}}_{.10}$ RATIO = <u>DISTANCE</u> MOUNTING HEIGHT <u>HEIGHT</u> <u>8' 10' 12' 14'</u> CORRECTION <u>1.6 1.2 1.0 .69</u>	Ballast/Lamps: CF13-26; HPS35-250; MH50-250; LED35W Voltage: 120; 208; 240; 277 Options: Refractor, Black-out Panel, Finial
QUICK REFRENCE SPACING GUIDE	HPS LAMP 35 50 70 100 150 250 CORRECTION .14 .25 .36 .59 1.00 1.72 MH LAMP 50 70 100 175 250 CORRECTION .18 .31 .53 .88 1.28 LAMP 13 26 COM FL CORRECTION .05 .10 LAMP 30 57 LED CORRECTION 1.10 1.20