

4400 NW 19th Avenue, Unit K Pompano Beach, FL 33064 (305) 895-9525 www.terracastproducts.com

JUPITER 4D POLE SPECIFICATIONS

Pole Material: Aluminum Smooth Extrusion

Wall Thickness: .125

E.P.A: 1.0

Wind Load Factor: 140 MPH

Base Material: Template mounting plate is solid

Cast Aluminum 26" high, 12" wide.
Post fitter is ½" thick, 3½" deep. Mounting seat for anchor bolts is 1/2"

thick.

Post Assembly: Pole is force fit into sleeve and is

reinforced by 1" weld all around.

Mounting: Supplied with four (4) "L" shaped 16" x $\frac{1}{2}$ "

> Hot Dipped Galvanized Bolts. Supplied is bolt Pattern for setting anchor bolts in

cement.


Access Plate: Access Door is cast aluminum 3 ½"x 6 ½",


½" thick.


Reducer: 4" to 3" reducer supplied with all

poles.

Bolt pattern 5½" cc.









Colors:

Available Heights:

Center Post:

Base:





All 52 Colors, Powder Coating Available Contact

8', 10', 12', 14'

Factory.

4" Diameter

26" Height

12" Width

Door is 3 ½"x 6 ½".