

## 4400 NW 19th Avenue, Unit K Pompano Beach, FL 33064 (305) 895-9525 www.terracastproducts.com

## PENNSYLVANIAN C POLE SPECIFICATIONS

<u>Pole Material:</u> <u>Wall Thickness:</u>	Aluminum Smooth Extrusion	<u>Colors:</u>	All 52 Colors, Powder Coating Available Contact
vvun internesse			Factory.
<u>E.P.A:</u>	1.0	Available Heights:	8′, 10′, 12′, 14′
Wind Load Factor:	140 MPH	Center Post:	3″ Diameter
<u>Base Material:</u>	Template mounting plate is solid Cast Aluminum 33" high, 10 $\frac{1}{4}$ " wide. Post fitter is $\frac{1}{2}$ " thick, 3 $\frac{1}{2}$ " deep. Mounting seat for anchor bolts is $\frac{1}{2}$ " thick.	<u>Base:</u>	33" Height 10 ¼" Width
Post Assembly:	Pole is force fit into sleeve and is reinforced by 1" weld all around.		
<u>Mounting:</u>	Supplied with four (4) "L" shaped $16" \times \frac{1}{2}"$ Hot Dipped Galvanized Bolts. Supplied is bolt Pattern for setting anchor bolts in cement.		
<u>Access Plate:</u>	Access Door is cast aluminum 5 ½"x 6 ½" , ½" thick.		
Bolt pattern 6	" сс.		

10 ¼"

3"

7"

Door is 5 ½"x 6 ½".

View From Above Template

 $\cap$