

4400 NW 19th Avenue, Unit K Pompano Beach, FL 33064 (305) 895-9525 www.terracastproducts.com

SAVANNAH 4G POLE SPECIFICATIONS

Colors:

Available Heights:

Center Post:

Base:

Pole Material: Aluminum Smooth Extrusion

Wall Thickness: .125

<u>E.P.A:</u> 1.0

Wind Load Factor: 140 MPH

Base Material: Template mounting plate is solid

Cast Aluminum 29 $\frac{1}{2}$ " high, 11 $\frac{1}{4}$ " wide. Post fitter is $\frac{1}{2}$ " thick, 3 $\frac{1}{2}$ " deep. Mounting seat for anchor bolts is $\frac{1}{2}$ "

thick.

Post Assembly: Pole is force fit into sleeve and is

reinforced by 1" weld all around.

Mounting: Supplied with four (4) "L" shaped 16" x ½"

Hot Dipped Galvanized Bolts. Supplied is bolt Pattern for setting anchor bolts in


cement.

Access Plate: Access Door is cast aluminum 5"x 5 ½",


½" thick.

Reducer: 4" to 3" reducer supplied with all poles.

Bolt pattern 51/2" cc.









Door is 5"x 5 ½".



All 52 Colors, Powder Coating Available Contact

8', 10', 12', 14'

Factory.

4" Diameter

29 ½" Height

11 ¼" Width