

4400 NW 19th Avenue, Unit K Pompano Beach, FL 33064 (305) 895-9525 www.terracastproducts.com

STAFFORD E2 POLE SPECIFICATIONS

Colors:

Available Heights:

Center Post:

Base:

Pole Material: Aluminum Smooth Extrusion

Wall Thickness: .250

<u>E.P.A:</u> 1.0

Wind Load Factor: 140 MPH

Base Material: Template mounting plate is solid

Cast Aluminum 13 $\frac{1}{2}$ " high, 10 $\frac{1}{4}$ " wide. Post fitter is $\frac{1}{2}$ " thick, 3 $\frac{1}{2}$ " deep. Mounting seat for anchor bolts is $\frac{1}{2}$ "

thick.

Post Assembly: Pole is force fit into sleeve and is

reinforced by 1" weld all around.

Mounting: Supplied with four (4) "L" shaped 16" x ½"


Hot Dipped Galvanized Bolts. Supplied is bolt Pattern for setting anchor bolts in


cement.

Access Plate: Access Door is cast aluminum 5 ½" x 6 ½" ,

½" thick.

Bolt pattern 6" cc.











All 52 Colors, Powder Coating Available Contact

8', 10', 12', 14'

Factory.

3" Diameter

13 ½" Height

10 ¼" Width

Door is 5 ½" x 6 ½"